



## Universalklemmen



**Pollmann**  
Elektrotechnik

## Universalklemmen



### Universalklemmen

- Montage auf 35 mm Tragschiene gem. EN 60715
- Für Anwendungen mit Kupfer- und Aluminiumleitungen
- Klemmkörper aus Alu, verzinkt

### Universal terminals

- to be mounted on 35 mm DIN rails acc. to EN 60715
- to be used with copper and aluminium wire
- terminal made of tin plated aluminium

### Terminaux universelles

- pour assemblage sur rail DIN de 35 mm selon EN 60715
- pour câbles d'aluminium et de cuivre
- borne de connexion en aluminium étamé

	Produktbezeichnung description description du produit	Artikel-Nr. code no. N° article	VPE p. u. unité	Klemmstellen connections connexions	Nennstrom nominal voltage	Querschnitt cross section section mm <sup>2</sup>
1-fach / 1-fold / 1-prises	UK 50/1 A grau / grey / gris	209 01 04	10	2	Al 145 A Cu 160 A	6,0 - 50 2,5 - 50
	UK 50/1 N blau / blue / bleu	209 01 05	10			
	UK 50/1 PE grün-gelb / green-yellow / vert-jaune	209 01 06	10			
	UK 95/1 A grau / grey / gris	209 01 07	8	2	Al 220 A Cu 245 A	16 - 95 16 - 95
	UK 95/1 N blau / blue / bleu	209 01 08	8			
	UK 95/1 PE grün-gelb / green-yellow / vert-jaune	209 01 09	8			
	UK 150/1 A grau / grey / gris	209 01 13	5	2	Al 290 A Cu 320 A	35 - 150 35 - 150
	UK 150/1 N blau / blue / bleu	209 01 14	5			
	UK 150/1 PE grün-gelb / green-yellow / vert-jaune	209 01 15	5			
	UK 240/1 A grau / grey / gris	209 01 16	2	2	Al 380 A Cu 425 A	35 - 240 35 - 240
	UK 240/1 N blau / blue / bleu	209 01 17	2			
	UK 240/1 PE grün-gelb / green-yellow / vert-jaune	209 01 18	2			
2-fach / 2-fold / 2-prises	UK 50/2 A grau / grey / gris	209 02 01	6	4	Al 145 A Cu 160 A	6,0 - 50 2,5 - 50
	UK 50/2 N blau / blue / bleu	209 02 02	6			
	UK 50/2 PE grün-gelb / green-yellow / vert-jaune	209 02 03	6			
	UK 95/2 A grau / grey / gris	209 02 04	3	4	Al 220 A Cu 245 A	16 - 95 16 - 95
	UK 95/2 N blau / blue / bleu	209 02 05	3			
	UK 95/2 PE grün-gelb / green-yellow / vert-jaune	209 02 06	3			
	UK 150/2 A grau / grey / gris	209 02 10	2	4	Al 290 A Cu 320 A	35 - 150 35 - 150
	UK 150/2 N blau / blue / bleu	209 02 11	2			
	UK 150/2 PE grün-gelb / green-yellow / vert-jaune	209 02 12	2			
	UK 240/2 A grau / grey / gris	209 02 13	1	4	Al 380 A Cu 425 A	35 - 240 35 - 240
	UK 240/2 N blau / blue / bleu	209 02 14	1			
	UK 240/2 PE grün-gelb / green-yellow / vert-jaune	209 02 15	1			
3-fach / 3-fold / 3-prises	UK 50/3 A grau / grey / gris	209 03 04	4	6	Al 145 A Cu 160 A	6,0 - 50 2,5 - 50
	UK 50/3 N blau / blue / bleu	209 03 05	4			
	UK 50/3 PE grün-gelb / green-yellow / vert-jaune	209 03 06	4			
	UK 95/3 A grau / grey / gris	209 03 07	2	6	Al 220 A Cu 245 A	16 - 95 16 - 95
	UK 95/3 N blau / blue / bleu	209 03 08	2			
	UK 95/3 PE grün-gelb / green-yellow / vert-jaune	209 03 09	2			
	UK 150/3 A grau / grey / gris	209 03 10	3	6	Al 290 A Cu 320 A	35 - 150 35 - 150
	UK 150/3 N blau / blue / bleu	209 03 11	3			
	UK 150/3 PE grün-gelb / green-yellow / vert-jaune	209 03 12	3			
	UK 240/3 A grau / grey / gris	209 03 13	1	6	Al 380 A Cu 425 A	35 - 240 35 - 240
	UK 240/3 N blau / blue / bleu	209 03 14	1			
	UK 240/3 PE grün-gelb / green-yellow / vert-jaune	209 03 15	1			